



PLUG-IN Line

X-CH	ATEX					
4x88	В LED - 7м	_				
T-ZE	ROPRO			FEATURES		
			• A	ATEX lighting	hting tower for explosive areas	
			max height 7 m	Multi-direction	nally adjustable and tiltable floodlights	
			7 m •	5 sections hyd	draulic vertical tower 7m, 340° rotatable	
		Wr.	kg .		g system by winch complete aking system	
				Galvanized metalworks		
T				80 µm powde	r coating	
			 Very compact dimensions for easy handling & transportability, up to 33 units per truck 			
				Light weight for improved manoeuvrability		
				Central lifting eye, forklift pockets for effective handling		
			rotation	Armored cable c/w plug to light up the unit		
				Certified wind stability up tp 110 km/h		
				4 extendable & height adjustable stabilizers		
					l levels for guidance during stabilization	
					ented mast emergency brake which prevents	
				the falling of the mast in case of cable failure		
a patented mast emergence improve safety of the operat					n he first lighting tower in the market that has patented mast emergency brake system to mprove safety of the operators on site egistration number: 102017000044431	
ZERO emissions	Sions fuel costs Image: Sevice fuel costs Image: Sevice Image: Sevice Image: Sevice Image: Sevice<					
LINKABLE TOWERS	2600 sqm illuminated area	EAS hand	SY A dling & transportability	8 HOURS A D 7 DAYS A WE		
Dimensions & weight			Dimensions max(mm)		Total weight (kg)	
	1200x850x2100 (LxWxH) 1850x1		1850x1450x7000 (L)	0 (LxWxH) 330		
Floodlights ATEX	Туре	Power (each)	Floodlights numbe	er IP level	Illuminated area (sqm)	
	Led	88W	4	66	2600	
Mast	Lifting method	Max Height	Max Wind Speed	Rotation	Patented mast emergency system	
	Manual	7 m	110 km/h	340°	yes	
Input&output	Inlet plug	nlet plug		tod	Trailer type	
	16A - 230V General		Manual		Hand trolley	
				-		

