


LED TECHNOLOGY

2200 sqm
Illuminated area

ENGINE POWERED Line



Operation: **ENGINE POWERED**
fuel tank capacity 81 litres
Kohler KD15/440


X-TR
2x150W LED-8M

X-TR 2X150W LED-8M



FEATURES

- Built-in toilette
- Built-in 6kVA Single-phase generator
- Fresh water level gauge
- Waste water level gauge
- Bathroom light
- Technical room light
- Telescopic ladder for floodlights regulation
- Road trailer
- Removable ladder for easy and safe bathroom entrance
- 4 sides lifting eyes
- 2 Multi-directionally adjustable and tiltable by hands floodlights
- 8mt hydraulic vertical telescopic mast
- Galvanized metalworks
- 80 µm powder coating
- Forklift pockets for effective handling
- Guided main coiled cable to avoid damage during tower operation
- 4 drop down stabilizers



General		Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)					
		3446x2268x3054 (LxWxH)		3446x2268x8000 (LxWxH)		1770					
Floodlights		Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)					
		LED	150W	2	65	2200					
Mast		Lifting method		Max Height		Max Wind Speed					
		Hydraulic		8 m		110 km/h					
Generator		Model		Rated output		Rated frequency		Rated voltage			
		Synchronous		6 kVA		50 Hz		230 V			
Engine	Model	Cylinders	Fuel	r.p.m.	Fuel tank (l)	Consumption (l/h)	Running time (h)	Start	Displacement	Oil sump capacity (l)	Cooling system
	Kohler KD 15/440	1	Diesel	3000	81	0,55	162	Electric	442 cm ³	1,5	air
Water		Waste water tank capacity (l)		Fresh water tank capacity (l)		Cold water		Capacity (l)		Recirculating flush tank (l)	
		95		95		yes		36		160	