INDUSTRIAL LINE



GENSET MODEL		
Code		P199-100TS0
Mechanical version	steel she canopy, co	version with galvanized et and powder-painted ompact base frame, with ank and leak control
Fuel Tank Capacity	lt.	160
Rated technical data		
Prime Power (PRP)	kVA	100
Prime Power (PRP)	KW	80
Limited Power (LTP)	kVA	110
Limited Power (LTP)	KW	88
Rated Power Factor (cosф)		0.8
Windings		Three phases Series Star
Rated three-phase concatenated Voltage	V	400
Rated phase-neutral voltage	V	230
Rated frequency	Hz	50
Fuel type		Diesel
Dimensions And Noise		
Length	mm	2560
Width	mm	1040
Height	mm	1805
Weight	Kg	1600
Sound pressure 7 m.	dBA	65
Fuel consumption		
Fuel Cons. at 100% (LTP)	l/h	24,4
Fuel Cons. at 100% (PRP)	l/h	22
Fuel Cons. at 75% (PRP)	l/h	15,3
Fuel Cons. at 50% (PRP)	l/h	11
General Alternator Data		
Alternator brand		STAMFORD
Alternator model		UCI274C
PRP Power	kVA	100
LTP Power	kVA	110
Winding		Three phases Series Star
Terminals Number		12 nr
IP Protection		23
Electronic regulator		SX460
Precision		± 1.50 %

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only. Northern

General Engine Data Engine brand FPT IVECO Engine model N45TM2A 4 Cylinders R.P.M. 1500 4500 Cubic capacity Air intake Turbo 12 Standard voltage Vdc Sae BMEP kPa 1584 Cooling Water Flywheel P.R.P. Power kW 87,5 Flywheel Stand-by Power kW 96,2 Electronic regulator On request Precision class G2 Oil quantity 12,8 lt. EU Stage STAGE 2 **Standard Features** Hard wires connection protected Electrical panel DSE 4520 mounted on board with safety cover Circuit breaker Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter 12V Battery with battery switch Bunded tank Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater KIT socket TPS01: 1x32A, 1x16A 3Ph 1x16A 1Ph + 1x16A Schuko

KIT socket TPS03:	1x63A, 1x32A, 1x16A 3Ph 1x16A 1Ph + 1x16A Schuko 125A breaker with adj. earth fault relay
Kit AMF and ATS pa	anel

Predisposition for quick release fitting for external fuel tank Oversize fuel tank



27030 Villanova D'Ardenghi (PV) Italy • Via Roma 6 Tel. +39 02 942 1464 • Sales Dept. +39 0382 406 252

MGTP 100 SS FI