

W.G.	4 7 11				
GENSET MODEL					
Code	IP200-120TS0				
		version with galvanized			
Mechanical version		steel sheet and powder-painted			
		canopy, compact base frame, with bunded tank and leak control			
Fuel Tank Capacity	lt.	160			
Rated technical data					
Prime Power (PRP)	kVA	124			
Prime Power (PRP)	KW	99,2			
Limited Power (LTP)	kVA	135			
Limited Power (LTP)	KW	108			
Rated Power Factor (cosφ)		0.8			
` ',		Three phases			
Windings		Series Star			
Rated three-phase		400			
concatenated Voltage	V	400			
Rated phase-neutral voltage	V	230			
Rated frequency	Hz	50			
Fuel type		Diesel			
Dimensions And Noise					
Length	mm	2560			
Width	mm	1040			
Height	mm	1805			
Weight	Kg	1690			
Sound pressure 7 m.	dBA	68			
Fuel consumption					
Fuel Cons. at 100% (LTP)	l/h	30,4			
Fuel Cons. at 100% (PRP)	l/h	27,6			
Fuel Cons. at 75% (PRP)	l/h	20,4			
Fuel Cons. at 50% (PRP)	I/h	14,4			
General Alternator Data	,	,			
Alternator brand		STAMFORD			
Alternator model		UCI274E			
PRP Power	kVA	140			
LTP Power	kVA	150			
		Three phases			
Winding		Series Star			
Terminals Number		12 nr			
IP Protection		23			
Electronic regulator		SX460			
Precision		± 1.50 %			

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



	General Engine Data		
	Engine brand		FPT IVECO
	Engine model		N45TM3
	Cylinders		4
	R.P.M.		1500
	Cubic capacity		4500
	Air intake		Turbo
	Standard voltage	Vdc	12
	Sae		-
	BMEP	kPa	1937
	Cooling		Water
	Flywheel P.R.P. Power	kW	107,2
	Flywheel Stand-by Power	kW	118,2
	Electronic regulator		On request
	Precision class		G2
	Oil quantity	lt.	12,8
	EU Stage		Not available

Standard Features Hard wires connection protected

Electrical panel ComAp AMF25 mounted on board with safety cover Circuit breaker

Internal exhaust gas silencer and insulated manifold

Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph

1x16A 1Ph + 1x16A Schuko

1x63A, 1x32A, 1x16A 3Ph

KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko

125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank

