INDUSTRIAL LINE



GENSET MODEL			
Code	I	P202-170TS0	
Mechanical version	steel shee canopy, co	Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control	
Fuel Tank Capacity	lt.	360	
Rated technical data			
Prime Power (PRP)	kVA	174	
Prime Power (PRP)	KW	139,2	
Limited Power (LTP)	kVA	191	
Limited Power (LTP)	KW	152,8	
Rated Power Factor (cosф)		0.8	
Windings		Three phases Series Star	
Rated three-phase concatenated Voltage	V	400	
Rated phase-neutral voltage	V	230	
Rated frequency	Hz	50	
Fuel type		Diesel	
Dimensions And Noise			
Length	mm	3060	
Width	mm	1140	
Height	mm	2230	
Weight	Kg	2050	
Sound pressure 7 m.	dBA	68	
Fuel consumption			
Fuel Cons. at 100% (LTP)	l/h	42,2	
Fuel Cons. at 100% (PRP)	l/h	36,6	
Fuel Cons. at 75% (PRP)	l/h	27,5	
. ,			
Fuel Cons. at 50% (PRP)	l/h	18	
General Alternator Data		CTANAGODD	
Alternator brand		STAMFORD	

Alternator brand		STAMFORD
Alternator model		UCI274G
PRP Power	kVA	180
LTP Power	kVA	194
Winding		Three phases Series Star
Terminals Number		12 nr
IP Protection		23
Electronic regulator		SX460
Precision		± 1.50 %

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



General Engine Data		
Engine brand		FPT IVECO
Engine model		N67TM4
Cylinders		6
R.P.M.		1500
Cubic capacity		6700
Air intake		Turbo
Standard voltage	Vdc	12
Sae		-
BMEP	kPa	1850
Cooling		Water
Flywheel P.R.P. Power	kW	149,7
Flywheel Stand-by Power	kW	165
Electronic regulator		On request
Precision class		G3
Oil quantity	lt.	17,2
EU Stage		Not available

Standard Features

Hard wires connection protected Electrical panel ComAp AMF25 mounted on board with safety cover Circuit breaker Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter 12V Battery with battery switch Bunded tank Lifting hooks and side forklift pockets Options factory installed 220V Electric pre-heater 1x32A, 1x16A 3Ph KIT socket TPS01: 1x16A 1Ph + 1x16A Schuko 1x63A, 1x32A, 1x16A 3Ph KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko 125A breaker with adj. earth fault relay Kit AMF and ATS panel Predisposition for quick release fitting for external fuel tank Oversize fuel tank

27030 Villanova D'Ardenghi (PV) Italy • Via Roma 6 Tel. +39 02 942 1464 • Sales Dept. +39 0382 406 252

www.trime.it info@trime.it

MGTP 170 SS FI