



GENSET MODEL

Code IP226-670TS0

Mechanical version Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bundled tank and leak control

Fuel Tank Capacity lt. 950

Rated technical data

Prime Power (PRP) kVA 670

Prime Power (PRP) KW 536

Limited Power (LTP) kVA 720

Limited Power (LTP) KW 576

Rated Power Factor (cosφ) 0.8

Windings Three phases
Series Star

Rated three-phase concatenated Voltage V 400

Rated phase-neutral voltage V 230

Rated frequency Hz 50

Fuel type Diesel

Dimensions And Noise

Length mm 5520

Width mm 1860

Height mm 2570

Weight Kg 6100

Sound pressure 7 m. dBA 74

Fuel consumption

Fuel Cons. at 100% (LTP) l/h 143

Fuel Cons. at 100% (PRP) l/h 132

Fuel Cons. at 75% (PRP) l/h 97

Fuel Cons. at 50% (PRP) l/h 66

General Alternator Data

Alternator brand STAMFORD

Alternator model HCI5F

PRP Power kVA 670

LTP Power kVA 738

Winding Three phases
Series Star

Terminals Number 12 nr.

IP Protection 23

Electronic regulator AS440

Precision ± 1.00 %

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.

General Engine Data

Engine brand PERKINS

Engine model 2806A-E18TAG2

Cylinders 6

R.P.M. 1500

Cubic capacity 18130

Air intake Turbo

Standard voltage Vdc 24

Sae 0 - 18

BMEP kPa 2576

Cooling Water

Flywheel P.R.P. Power kW 565

Flywheel Stand-by Power kW 609

Electronic regulator Standard

Precision class G3

Oil quantity lt. 62

EU Stage Non emission certified

Standard Features

Hard wires connection protected

Electrical panel ComAp AMF25 mounted on board with safety cover

Circuit breaker

Internal exhaust gas silencer and insulated manifold

Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bundled tank

Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph
1x16A 1Ph + 1x16A Schuko

KIT socket TPS03: 1x63A, 1x32A, 1x16A 3Ph
1x16A 1Ph + 1x16A Schuko
125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank