INDUSTRIAL LINE

MGTP 100 S<u>S PI</u>

89 Perkins[®]

GENSET MODEL			
Code	I	P214-100TS0	
Mechanical version	steel shee canopy, co	Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control	
Fuel Tank Capacity	lt.	160	
Rated technical data			
Prime Power (PRP)	kVA	100	
Prime Power (PRP)	KW	80	
Limited Power (LTP)	kVA	110	
Limited Power (LTP)	KW	88	
Rated Power Factor (cosф)		0.8	
Windings		Three phases Series Star	
Rated three-phase concatenated Voltage	V	400	
Rated phase-neutral voltage	V	230	
Rated frequency	Hz	50	
Fuel type		Diesel	
Dimensions And Noise			
Length	mm	2560	
Width	mm	1040	
Height	mm	1850	
Weight	Kg	1650	
Sound pressure 7 m.	dBA	65	
Fuel consumption			
Fuel Cons. at 100% (LTP)	l/h	24,9	
Fuel Cons. at 100% (PRP)	l/h	22,6	
Fuel Cons. at 75% (PRP)	l/h	17,1	
Fuel Cons. at 50% (PRP)	I/h	11,2	
General Alternator Data	,	,	
Alternator brand		STAMFORD	
Alternator model		UCI274C	
PRP Power	kVA	100	
LTP Power	kVA	110	
Winding		Three phases Series Star	
Terminals Number		12 nr.	
IP Protection		23	
Electronic regulator		SX460	
Precision		± 1.50 %	

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.





	General Engine Da	ita									
	Engine brand			PERKINS							
	Engine model			1104C-44TAG2							
	Cylinders			4							
	R.P.M.			1500							
	Cubic capacity			4400							
	Air intake			Turbo							
	Standard voltage		Vdc	12							
	Sae			-							
	BMEP		kPa	1702							
	Cooling			Water							
	Flywheel P.R.P. Pow	/er	kW	89							
	Flywheel Stand-by	Power	kW	97,9							
	Electronic regulato	r		Standard							
	Precision class			G3							
	Oil quantity		lt.	8							
	EU Stage			STAGE 2							
Standard Features											
Hard wires connection protected											
Electrical panel DSE 4520 mounted on board with safety cover Circuit breaker Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter											
						12V Battery with battery switch					
						Bunded tank Lifting hooks and side forklift pockets					
	KIT socket TPS01: 1x32A, 1x16A 3Ph 1x16A 1Ph + 1x16A Schuko										
1x63A, 1x32A, 1x16A 3Ph KIT socket TPSO3: 1x16A 1Ph + 1x16A Schuko 125A breaker with adj. earth fault relay											
	Kit AMF and ATS pa										
	Predisposition for quick release fitting for external fuel tank										
Oversize fuel tank											

27030 Villanova D'Ardenghi (PV) Italy • Via Roma 6 Tel. +39 02 942 1464 • Sales Dept. +39 0382 406 252

www.trime.it info@trime.it