## **INDUSTRIAL LINE**

## MGTP 150 SS <u>PI</u>

88 Perkins<sup>®</sup>

GENSET MODEL		
Code	T	P216-150TS0
Mechanical version	steel shee canopy, co	version with galvanized et and powder-painted ompact base frame, with ink and leak control
Fuel Tank Capacity	lt.	360
Rated technical data		
Prime Power (PRP)	kVA	150
Prime Power (PRP)	KW	120
Limited Power (LTP)	kVA	165
Limited Power (LTP)	KW	132
Rated Power Factor (cos p)		0.8
Windings		Three phases Series Star
Rated three-phase concatenated Voltage	V	400
Rated phase-neutral voltage	V	230
Rated frequency	Hz	50
Fuel type		Diesel
Dimensions And Noise		
Length	mm	3060
Width	mm	1140
Height	mm	2230
Weight	Kg	2320
Sound pressure 7 m.	dBA	70
Fuel consumption		
Fuel Cons. at 100% (LTP)	l/h	36,1
Fuel Cons. at 100% (PRP)	l/h	33,4
Fuel Cons. at 75% (PRP)	l/h	24,7
Fuel Cons. at 50% (PRP)	l/h	16,4
General Alternator Data	,	,
Alternator brand		STAMFORD
Alternator model		UCI274F
PRP Power	kVA	160
LTP Power	kVA	175
Winding		Three phases Series Star
Terminals Number		12 nr.
IP Protection		23
Electronic regulator		SX460
Precision		± 1.50 %

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.

General Engine Da	ata			
Engine brand			PERKINS	
Engine model			1106A-70TAG2	
Cylinders			6	
R.P.M.			1500	
Cubic capacity			7010	
Air intake			Turbo	
Standard voltage		Vdc	12	
Sae			-	
BMEP		kPa	1552	
Cooling			Water	
Flywheel P.R.P. Pov	ver	kW	131	
Flywheel Stand-by	Power	kW	144,1	
Electronic regulate	or		On request	
Precision class			G2	
Oil quantity		lt.	16,5	
EU Stage			Not available	
Standard Features	;			
Hard wires connection protected				
Electrical panel ComAp AMF25 mounted on board with safety cover				
Circuit breaker				
Internal exhaust gas silencer and insulated manifold				
Engine oil extraction pump and fuel decanter filter				
12V Battery with battery switch				
Bunded tank				
Lifting hooks and side forklift pockets				
Options factory installed				
220V Electric pre-heater				
KIT socket TPS01:	1x32A, 1x16A 3Ph 1x16A 1Ph + 1x16A Schuko			
1x63A, 1x32A, 1x16A 3Ph KIT socket TPSO3: 1x16A 1Ph + 1x16A Schuko 125A breaker with adj. earth fault relay				
Kit AMF and ATS pa	anel			
Predisposition for quick release fitting for external fuel tank				
Predisposition for	quick release fitting	g for ext	ernal fuel tank	



27030 Villanova D'Ardenghi (PV) Italy • Via Roma 6 Tel. +39 02 942 1464 • Sales Dept. +39 0382 406 252

www.trime.it info@trime.it