INDUSTRIAL LINE

MGTP 40 SS PI

BPerkins[®]

GENSET MODEL		
Code Mechanical version	IP210-40TS0 Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control	
Fuel Tank Capacity	lt. 160	
Rated technical data		
Prime Power (PRP)	kVA 40	
Prime Power (PRP)	KW 32	
Limited Power (LTP)	kVA 44	
Limited Power (LTP)	KW 35,2	
Rated Power Factor (cosф)	0.8	
Windings	Three phases Series Star	
Rated three-phase concatenated Voltage	V 400	
Rated phase-neutral voltage	V 230	
Rated frequency	Hz 50	
Fuel type	Diesel	
Dimensions And Noise		
Length	mm 2260	
Width	mm 1040	
Height	mm 1820	
Weight	Kg 1240	
Sound pressure 7 m.	dBA 61	
Fuel consumption		
Fuel Cons. at 100% (LTP)	l/h 12	
Fuel Cons. at 100% (PRP)	l/h 10,7	
Fuel Cons. at 75% (PRP)	l/h 8,2	
Fuel Cons. at 50% (PRP)	l/h 5,7	
General Alternator Data		
Alternator brand	STAMFORD	
Alternator model	S1L2-K	
PRP Power	kVA 40	
LTP Power	kVA 44	
Winding	Three phases Series Star	
Terminals Number	12 nr.	
IP Protection	23	
Electronic regulator	AS540	
Precision	± 1.00 %	
The company reserves the right to moo and design without notice.	lify the technical specifications, item	ns

The images of the products are indicative for illustrative purposes only.



	110			
General Engine Data				
Engine brand		PERKINS		
Engine model		1103A-33TG1		
Cylinders		3		
R.P.M.		1500		
Cubic capacity		3300		
Air intake		Turbo		
Standard voltage	Vdc	12		
Sae		-		
BMEP	kPa	1023		
Cooling		Water		
Flywheel P.R.P. Power	kW	41,3		
Flywheel Stand-by Power	kW	45,6		
Electronic regulator		On request		
Precision class		G2		
Oil quantity	lt.	8,3		
EU Stage		Not available		
Standard Features				
Hard wires connection protected				
Electrical panel DSE 4520 mounted on board with safety cover				
Circuit breaker				
Internal exhaust gas silencer and insulated manifold				
Engine oil extraction pump and fuel decanter filter				
12V Battery with battery switch				
Bunded tank				
Lifting hooks and side forklift pockets				

Options factory installed

220V Electric pre-heaterKIT socket TPS01:1x32A, 1x16A 3Ph
1x16A 1Ph + 1x16A SchukoKIT socket TPS03:1x63A, 1x32A, 1x16A 3Ph
1x16A 1Ph + 1x16A Schuko
125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank Oversize fuel tank



27030 Villanova D'Ardenghi (PV) Italy • Via Roma 6 Tel. +39 02 942 1464 • Sales Dept. +39 0382 406 252