## **INDUSTRIAL LINE**

## MGTP 600 SS PI

PERKINS

6

1500

18130

2806C-E18TAG1A

**Perkins**<sup>®</sup>

GENSET MODE

GENSET MODEL			
Code		P225-600TS0	
Mechanical version	steel she canopy, co	Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control	
Fuel Tank Capacity	lt.	950	
Rated technical data			
Prime Power (PRP)	kVA	600	
Prime Power (PRP)	KW	480	
Limited Power (LTP)	kVA	660	
Limited Power (LTP)	KW	528	
Rated Power Factor (cosф)		0.8	
Windings		Three phases Series Star	
Rated three-phase concatenated Voltage	V	400	
Rated phase-neutral voltage	V	230	
Rated frequency	Hz	50	
Fuel type		Diesel	
Dimensions And Noise			
Length	mm	4500	
Width	mm	1840	
Height	mm	2540	
Weight	Kg	5710	
Sound pressure 7 m.	dBA	74	
Fuel consumption			
Fuel Cons. at 100% (LTP)	l/h	134	
Fuel Cons. at 100% (PRP)	l/h	129	
Fuel Cons. at 75% (PRP)	l/h	96	
Fuel Cons. at 50% (PRP)	l/h	63	
General Alternator Data			
Alternator brand		STAMFORD	
Alternator model		HCI5E	
PRP Power	kVA	610	
LTP Power	kVA	665	
Winding		Three phases Series Star	
Terminals Number		12 nr.	
IP Protection		23	
Electronic regulator		AS440	
Precision		± 1.00 %	
<b>T</b> I I I I I I I I I I I I I I I I I I I			

Air intake Turbo Standard voltage Vdc 24 Sae \_ BMEP kPa 2347 Cooling Water Flywheel P.R.P. Power kW 514 Flywheel Stand-by Power kW 565 Electronic regulator Standard Precision class G3 Oil quantity lt. 62 EU Stage STAGE 2 Standard Features Hard wires connection protected Electrical panel ComAp AMF25 mounted on board with safety cover Circuit breaker Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter 12V Battery with battery switch Bunded tank Lifting hooks and side forklift pockets **Options** *factory installed* 220V Electric pre-heater 1x32A, 1x16A 3Ph KIT socket TPS01: 1x16A 1Ph + 1x16A Schuko 1x63A, 1x32A, 1x16A 3Ph KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko 125A breaker with adj. earth fault relay Kit AMF and ATS panel Predisposition for quick release fitting for external fuel tank

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.



27030 Villanova D'Ardenghi (PV) Italy • Via Roma 6 Tel. +39 02 942 1464 • Sales Dept. +39 0382 406 252

Oversize fuel tank

General Engine Data Engine brand

Engine model

Cubic capacity

Cylinders

R.P.M.