## **Serkins**®

GENSET MODEL				
Code		IP213-80TS0		
Mechanical version	Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control			
Fuel Tank Capacity	lt.	160		
Rated technical data				
Prime Power (PRP)	kVA	80		
Prime Power (PRP)	KW	64		
Limited Power (LTP)	kVA	88		
Limited Power (LTP)	KW	70,4		
Rated Power Factor (cosφ)		0.8		
Windings		Three phases Series Star		
Rated three-phase concatenated Voltage	V	400		
Rated phase-neutral voltage	V	230		
Rated frequency	Hz	50		
Fuel type		Diesel		
Dimensions And Noise				
Length	mm	2260		
Width	mm	1040		
Height	mm	1820		
Weight	Kg	1500		
Sound pressure 7 m.	dBA	65		
Fuel consumption				
Fuel Cons. at 100% (LTP)	l/h	20,5		
Fuel Cons. at 100% (PRP)	l/h	18,7		
Fuel Cons. at 75% (PRP)	l/h	14		
Fuel Cons. at 50% (PRP)	l/h	9,7		
General Alternator Data				
Alternator brand		STAMFORD		
Alternator model		UCI224G		
PRP Power	kVA	85		
LTP Power	kVA	90,8		
Winding		Three phases Series Star		
Terminals Number		12 nr.		
IP Protection		23		
Electronic regulator		SX460		
Precision		± 1.50 %		

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



	General Engine Data				
	Engine brand		PERKINS		
	Engine model		1104A-44TG2		
	Cylinders		4		
	R.P.M.		1500		
	Cubic capacity		4400		
	Air intake		Turbo		
	Standard voltage	Vdc	12		
	Sae		-		
	BMEP	kPa	1335		
	Cooling		Water		
	Flywheel P.R.P. Power	kW	71,9		
	Flywheel Stand-by Power	kW	79,1		
	Electronic regulator		On request		
	Precision class		G2		
	Oil quantity	lt.	8		
	EU Stage		Not available		
	Standard Features				
Hard wires connection protected  Electrical panel DSE 4520 mounted on board with safety co					
	Internal exhaust gas silencer and insul	aust gas silencer and insulated manifold			
	Engine oil extraction pump and fuel de	filter			
	12V Battery with battery switch				
	Bunded tank				
Lifting hooks and side forklift pockets					

## Options factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph

1x16A 1Ph + 1x16A Schuko

1x63A, 1x32A, 1x16A 3Ph

KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko

125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank

