

# PORTABLE SILENCED LINE

GASOLINE

AIR COOLED ENGINE  
3000 r.p.m.



SINGLE phase



THREE phase

	MGTP 11 AE	MGTP 12 AE 3F
Code	PP79-11MS0	PP80-12TS0
<b>On board control panel equipped with:</b>		
	<ul style="list-style-type: none"> <li>- DSE ON/OFF switch</li> <li>- DSE 3110 module will display warnings, shutdowns &amp; engine status information as high temperature, low oil pressure, low fuel level warning, Volts &amp; Frequency, running hrs, battery voltage monitoring</li> <li>- Circuit breaker</li> <li>- Emergency Stop</li> <li>- Sounproof canopy</li> <li>- Exhaust gas silencer</li> <li>- 2x32A 1ph 230V EEC socket</li> <li>- 1x16A 1ph 230V EEC socket</li> </ul>	<ul style="list-style-type: none"> <li>- DSE ON/OFF switch</li> <li>- DSE 3110 module will display warnings, shutdowns &amp; engine status information as high temperature, low oil pressure, low fuel level warning, Volts &amp; Frequency, running hrs, battery voltage monitoring</li> <li>- Circuit breaker</li> <li>- Emergency Stop</li> <li>- Sounproof canopy</li> <li>- Exhaust gas silencer</li> <li>- 1x 16A 3Ph 400V EEC socket</li> <li>- 1x 32A 1Ph 230V EEC socket</li> <li>- 1x 16A 1Ph 230V EEC socket</li> </ul>
<b>Generator</b>		
Type	Linz E1C11M B	Linz E1S11M AS
<b>Power</b>	<b>11 kVA 230V</b>	<b>12 kVA 400V</b>
Frequency	50 Hz	50 Hz
<b>Engine</b>		
Engine type	HONDA GX630	HONDA GX630
N° cylinders	2	2
Power	20,8 HP	20,8 HP
Engine speed	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric
<b>Dimensions &amp; weight</b>		
Fuel tank capacity	21 lt	21 lt
Running Time	4,4 hrs	4,4 hrs
Dry weight	204 Kg	204 Kg
Dimensions (L. x W. x H.)	970 x 600 x 750 mm	970 x 600 x 750 mm

## OPTIONS

Site tow trailer    Road tow trailer    Trolley

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.