

**ELECTRIC START ENGINE  
3000 r.p.m.**



**HONDA**



**3000  
RPM**



LWA  
2000/14/CE

**NOISE  
Level**



**AIR  
cooled**



**GASOLINE**

**AVR**

**AUTOMATIC  
VOLTAGE  
REGULATOR**



**SINGLE phase**



**THREE phase**



**THREE phase**

	<b>MGTP 11 H BM AE</b>	<b>MGTP 11 H BT AE AVR</b>	<b>MGTP 11 H BT AE</b>
Code	<b>PP66-11M00</b>	<b>PP68-11T00</b>	<b>PP67-11T00</b>
<b>On board control panel equipped with:</b>			
	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket
<b>Generator</b>			
Type	Linz E1C11MB	Linz E1X13SB c/w AVR	Linz E1S10LL
<b>Power</b>	<b>11 kVA 230V</b>	<b>11 kVA 400V</b>	<b>11 kVA 400V</b>
Frequency	50 Hz	50 Hz	50 Hz
<b>Engine</b>			
Engine type	HONDA GX630	HONDA GX630	HONDA GX630
N° cylinders	2	2	2
Power	20,8 HP	20,8 HP	20,8 HP
Engine speed	3000 r.p.m.	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric	Electric
<b>Dimensions &amp; weight</b>			
Fuel tank capacity	13,3 lt	13,3 lt	13,3 lt
Running Time	2,8 hrs	2,8 hrs	2,8 hrs
Dry weight	123 Kg	130 Kg	130 Kg
Dimensions (L. x W. x H.)	780 x 520 x 750 mm	780 x 520 x 750 mm	780 x 520 x 750 mm

## OPTIONS

Site tow trailer  
  Road tow trailer  
  Trolley

The company reserves the right to modify the technical specifications, items and design without notice.  
The images of the products are indicative for illustrative purposes only.