

**MANUAL START ENGINE**  
**3000 r.p.m.**



**HONDA**



**3000 RPM**



**NOISE Level**  
LWA 2000/14/CE



**AIR cooled**



**GASOLINE**

**AVR** AUTOMATIC VOLTAGE REGULATOR



**SINGLE phase**



**SINGLE phase**



**SINGLE phase**

	<b>MGTP 3,5 H BM AS</b>	<b>MGTP 4,8 H BM AS AVR</b>	<b>MGTP 4,8 H BM AS</b>
Code	<b>PP58-4M00</b>	<b>PP60-5M00</b>	<b>PP59-5M00</b>
<b>On board control panel equipped with:</b>			
	- Hour counter - Volt meter - Main circuit breaker - 1x16A 1ph 230V EEC socket - 1x16A 1ph 230V Schucko socket	- Hour counter - Volt meter - Main circuit breaker - 1x16A 1ph 230V EEC socket - 1x16A 1ph 230V Schucko socket	- Hour counter - Volt meter - Main circuit breaker - 1x16A 1ph 230V EEC socket - 1x16A 1ph 230V Schucko socket
<b>Generator</b>			
Type	Linz E1C10SD	Linz E1C10SF c/w AVR	Linz E1E10MH
<b>Power</b>	<b>3,5 kVA 230V</b>	<b>4,8 kVA 230V</b>	<b>4,8 kVA 230V</b>
Frequency	50 Hz	50 Hz	50 Hz
<b>Engine</b>			
Engine type	HONDA GX160	HONDA GX270	HONDA GX270
N° cylinders	1	1	1
Power	4,8 HP	8,4 HP	8,4 HP
Engine speed	3000 r.p.m.	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline	Unleaded gasoline
Starting system	Manual recoil	Manual recoil	Manual recoil
<b>Dimensions &amp; weight</b>			
Fuel tank capacity	3,1 lt	5,3 lt	5,3 lt
Running Time	2,8 hrs	2,7 hrs	2,7 hrs
Dry weight	47 Kg	71 Kg	71 Kg
Dimensions (L. x W. x H.)	620 x 440 x 540 mm	760 x 520 x 620 mm	760 x 520 x 620 mm

### OPTIONS

- Site tow trailer
  Road tow trailer
  Trolley

The company reserves the right to modify the technical specifications, items and design without notice.  
The images of the products are indicative for illustrative purposes only.