PORTABLE SILENCED LINE

GASOLINE

AIR COOLED ENGINE
3000 r.p.m.

HONDA | 3000 RPM | NOISE level LWA 2000/14/CE | AIR cooled | GASOLINE

SINGLE phase

THREE phase

	MGTP 6 AE	MGTP 7 AE 3F
Code	**PP77-6MS0**	**PP78-7TS0**
On board control panel equipped with:		
	- DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Sounproof canopy - Exhaust gas silencer - 2x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Sounproof canopy - Exhaust gas silencer - 1x 16A 3Ph 400V EEC socket - 1x 32A 1Ph 230V EEC socket - 1x 16A 1Ph 230V EEC socket
Generator		
Type	Linz E1C10 M H	Linz E1S10M H
Power	**6 kVA 230V**	**7 kVA 400V**
Frequency	50 Hz	50 Hz
Engine		
Engine type	HONDA GX390	HONDA GX390
N° cylinders	1	1
Power	11 HP	11 HP
Engine speed	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric
Dimensions & weight		
Fuel tank capacity	21 lt	21 lt
Running Time	7 hrs	7 hrs
Dry weight	190 Kg	190 Kg
Dimensions (L. x W. x H.)	970 x 600 x 750 mm	970 x 600 x 750 mm

OPTIONS

- Trolley

The company reserves the right to modify the technical specifications, items and design without notice.
The images of the products are indicative for illustrative purposes only.

TRIME Power Division

27030 Villanova D'Ardenghi (PV) Italy • Via Roma 6
Tel. +39 02 942 1464 • Sales Dept. +39 0382 406 252

www.trime.it
info@trime.it